



# Art Line Care Instructions

## Surface Treatment:

Art Line can be delivered oiled, varnished or untreated.

The floor is treated with optional environmentally approved hard wax oil according to the manufacturer's instructions, which effectively protects the floor from dirt and wear. The oil gives a silky appearance that emphasizes the unique character of the wooden floor.

The surface is hypoallergenic, easy to clean and easy to maintain.

Art Line must be treated with caring oil before the floor is used.

## Installation:

Art Line can be delivered finished to save time during installation. However, we recommend an initial maintenance with Rubio monocoat.

## Renovation:

Art Line is perfect for renovation thanks to the thin thickness of 10 mm.

## Indoor climate:

It is very important that the surface temperature never exceeds 27°C.

The relative humidity (RH) must be between about 35-65%. 20 °C both before, during and after assembly.

## **Maintenance oiling with wax oil:**

- Make sure the surface is clean, and clean with Rubio Monocoat SOAP.
- Shake the can with Rubio Monocoat Universal Maintenance Oil well so that you get the bottom sediment.
- For large areas: Work two by two, one applies and one removes excess, you need two single scrubbers, a layer of red and white discs. Cloths to dry hands with etc.
- Use single scrubber and red pad to apply the oil, apply thinly. Max 5-10 m<sup>2</sup> at a time.
- Keep in mind that the oil is fast-hardening, at + 15 min it becomes as tough as chewing gum, we therefore recommend that you try to see how many m<sup>2</sup> you can do at a time. Don't take chances with too large surfaces.
- Have a bucket of water with you where you throw away oil-soaked rags, (this is due to the risk of fire in the event of self-ignition) this bucket SHOULD be out of the building at the end of the shift.
- Allow the surface to dry for at least 6 – 8 hours before using the surface.
- Use Rubio SOAP and water for any cleaning. This product must also be used when cleaning the floor after inauguration.
- The above recommendations are given based on Aprobo's long experience of cleaning and maintenance on large projects. We take no responsibility for how staff interpret the description or perform the work. For questions or concerns, contact us.

## Maintenance with varnish:

Make it a daily routine to remove visible dirt such as crumbs, grains of sand and the like. Vacuuming with a fixed brush nozzle removes most dry particles. Moisture drying with a tightly wrung-out microfiber cloth (mop) is carried out if necessary. A few drops of a mild synthetic detergent, such as hand washing detergent without ammonia, can be added to the water. Never use wet cleaning methods on a wooden floor!

### Stain removal:

Remove stains before they have had time to dry into the paint and, if necessary, re-dry with clean water. Use a well-wrung cloth. A varnished wooden floor is damaged by a lot of hot water, strong cleaning agents such as perchlorethylene, thinner, acetone and T-spirits. Therefore, use these stain removers with great care. ATTENTION! Sanding with steel wool and scouring nylon can scratch the paint.

### Stain guide:

Type of stain:	Remove with:
Chocolate, fat, fruit, ice cream, cream, juice, coffee, soda, juice, tea, wine, egg, beer, excrement, vomit, urine.	Neutral or slightly alkaline detergent without ammonia diluted in lukewarm water.
Asphalt, rubber, oil, shoe polish, soot, more difficult chocolate and grease stains.	Washing naphtha, lacquer naphtha.
Crayons, lipstick, marker.	Methylated Spirit 50%.
Stearin, chewing gum.	Apply cooling spray or place a plastic bag with ice cubes on the spot. Then scrape gently.
Blood.	Cold water.

### Contact us

+4610-183 31 80

info@aprobo.com

Sweden, Västra Vallgatan 2, SE-291 30 Kristianstad

