



Art Line Product Sheet

This is our latest addition to our solid wood floors. Art Line is a further development of the traditional industrial parquet that has been used for decades to create durable floors at low cost. For many years, the product has been interesting for its appearance and has therefore been moved into modern environments such as offices, schools and public buildings.

The problems with the traditional industrial parquet are that it requires extensive post-work during installation in the form of multiple sanding, filler filling and surface treatment. In some cases, this creates a lack of time in the construction projects and in other cases the product becomes difficult to handle as the parquet modules contain loose small rods.

Art Line offers a module that has fixed rods that provide an opportunity for processing and handling that greatly simplifies the laying, and above all where there is a lot of customization. The modules are also provided with a groove and tongue on all four sides and the module is carefully milled at an angle. The Art Line module is ground at the factory and surface treated with two layers of hard wax oil or a varnished surface, with or without pigmentation. In cases where it is delivered with hard wax oil, the surface is basically finished, but we recommend that an initial maintenance is carried out before the surface is put into use. It is also possible to order with varnish.

Within the Art Wood Collection, we offer a large selection of mosaic, block, industrial parquet, etc. These products are manufactured in Europe and as a rule, all production follows the European DIN standard for drying the wood (9+-2% RH). In Sweden, there is a drier climate that requires a lower moisture ratio to adapt the wood's movement during our seasonal changes and the AMA describes this as 7.5%+-1% RH. As the first product in this segment, we offer Art Line with an adapted moisture ratio corresponding to the AMA requirement.

Art Line is manufactured and handled in accordance with FCS and the surface treatment is carried out with hard wax oil and varnish that complies with the environmental requirements for our market. As standard, we offer the Art Line module with dimensions 10x245x490 mm.

We recommend using Art Parquet glue when applying. This glue is a so-called elastic SMP adhesive that does not contain water or solvents. The glue can be applied to moist substrates and by applying the glue as a film-forming layer, the glue works against moisture protection up to 85% RH.

Contact us

+4610-183 31 80

info@aprobo.com

Sweden, Västra Vallgatan 2, SE-291 30 Kristianstad

